

BOSE- PowerShare PS404D Adaptable Power Amplifier 230V EU



DESCRIPTION

Put the power where you need it. PowerShare amplifiers deliver outstanding audio performance and reliability with patented technologies inherited from the field-proven PowerMatch line – now with added flexibility. Using innovative PowerShare technology, the amp shares power across all output channels and delivers 400 watts for installed applications. This means you can distribute the total 400 watts asymmetrically across all outputs or use any individual output to deliver full power. And with support for both low- and high-impedance loads up to 100V, it's easy to adapt PowerShare amplifiers to a wide range of applications. ControlSpace Designer software allows for Ethernet-based configuration and quick setup of external control options. With onboard Dante® audio networking, you have the flexibility to place PowerShare amplifiers away from source locations and closer to loudspeakers. This unique set of features and technologies makes PowerShare one of the most versatile, high-performance amplifiers available today.

PowerShare Technology

Distribute the total 400 watts asymmetrically across all outputs using patented PowerShare technology, which allows each output to deliver full power. Instead of selecting amplifier power based on the needs of the largest zone, you now have the freedom to use total amplifier power in any application. This enables more flexibility during the initial design, or later on-site when making unplanned changes that take advantage of surplus power.

Load-independent Outputs

Configure any channel for low-impedance (4-8 Ω) or high-impedance (70/100V) applications without bridging or using jumpers.

Integrated Dante Audio Networking

Support four audio input channels from a Dante network and mix onboard analog inputs with digital Dante inputs as selected in ControlSpace Designer software.

Dual Feedback Loop System

Improve performance and reliability. The Dual Feedback Loop system, inherited from the field-proven Bose PowerMatch amplifier line, allows for continuous monitoring and control of both the current and voltage delivered to each output load. This combination provides improved linearity and lower distortion while protecting loudspeakers.

ControlSpace Networking

Configure using ControlSpace Designer software for inclusion into larger networked audio systems where end-user controllers and

scheduling events can control amplifier parameters.

Integrated Loudspeaker Processing
Adjust various parameters using ControlSpace Designer software: nine-band PEQs, matrix mixing, crossover, limiters, delay, mute/output polarity, and more.

Auto-standby
Save power PowerShare amplifiers can be configured to automatically enter standby mode when the audio signal falls below a set threshold, then wake when audio returns.

TECHNICAL CHARACTERISTICS

Brand : BOSE
Part number : 813375-2310
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Audio output channels : 4.0 channels
Connectivity technology : Wired
Depth : 414 mm
Ethernet LAN (RJ-45) ports : 1
Harmonized System (HS) code : 85184000
Height : 44 mm
Input impedance : 20
Maximum current : 14.14 A
On/off switch : Y
Peak power per channel : 400 W
Power consumption (standby) : 14 W
Product colour : Black
Signal-to-Noise Ratio (SNR) : 100 dB
Total Harmonic Distortion (THD) : 0.04%
Weight : 6.4 kg
Width : 483 mm