

HANWHA- 2MP IR Bullet+ AI Intrusion PRO



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNO-6020R-V/INT
Représentation / réalisation :
Type : IP security camera
Certification : NEMA 4X
Active tampering alarm : Yes
Alert notification type : E-mail
Anti-flicker : Yes
Audio detection : Yes
Audio formats supported : AAC-LC, ADPCM, G.711, G.726
Audio system : 2-way
Auto-tracking : Yes
Back Light Compensation (BLC) : Yes
Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Camera shutter speed : 2 - 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Yes
Closest focusing distance : 0.4 m
Compatible memory cards : SD, SDHC, SDXC
Composite video out : 1
Connectivity technology : Wired
Depth : 296 mm
Digital zoom : 24x
Ethernet interface type : Fast Ethernet
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Fixed focal length : 4 mm

Flip & mirror : Yes
Focus : Manual
Fog proof : Yes
Form factor : Bullet
Frame rate : 60 fps
Height : 70 mm
Highlight Compensation (HLC) : Yes
Housing material : Aluminium
IK code : IK10
Image quality adjustment : Contrast
Image stabilizer : Yes
Infrared (IR) cut-off filter : Yes
Intelligent Video Surveillance (IVS) system features : Crossing line, Defocus, Face detection, Missing object, People counting
International Protection (IP) code : IP66, IP67
IP address filtering : Yes
LED type : IR
Lens viewing angle, diagonal : 104.8°
Lens viewing angle, horizontal : 88.6°
Lens viewing angle, vertical : 47.5°
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum aperture number : 1.4
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Microphone in : Yes
Minimum illumination : 0.015 lx
Mounting type : Wall
Networking standards : IEEE 802.3af
Night vision : Yes
Night vision distance : 30 m
Noise reduction : Yes
Noise reduction technology : 3D noise reduction
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1109 pixels
Number of lenses : 1
Number of sensors : 1
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Indoor & outdoor
Power consumption (Power over Ethernet (PoE)) : 9.7 W
Power consumption (typical) : 8.8 W
Power source type : DC, PoE
Privacy masking : Yes
Product colour : Black
Progressive scan : Yes
Protection features : Vandal proof
PTZ control : Yes
PTZ modes : Digital PTZ
Quality of Service (QoS) support : Yes
Remote viewing : Yes
Sample rate : 48 kHz
Security algorithms : 802.1x RADIUS, EAP-TLS

Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Text caption overlay : Yes
Total megapixels : 2.16 MP
USB port : Yes
Video formats supported : AVC, H.264, H.265, M-JPEG, MPEG4
Video motion detection : Yes
Video streaming : Yes
Web browser : Yes
Weight : 1.22 kg
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Yes
Width : 70 mm
Windows operatin