

# Eaton EPDU MI 1U In: C20 16A 1P - Out: C13x8



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMIH28

### Design :

Type : Single-phase

### Caractéristiques :

Certification : CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011 Safety - Part 1: General Requirements, IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1 EN 55022:2010, EN 61000-6-2:2005 Part 6-2, EN 50581 : 2012, REACH, WEEE, PEP, ISO 9001:2008, ISO 14001:2004

AC input frequency : 50 Hz

AC outlet types : C13 coupler

AC outlets quantity : 8 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 482.6 mm

Dimensions (WxDxH) : 203 x 482.6 x 44.45 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 44.5 mm

Input connection type : IEC-320-C20

Management protocols : SNMP, Telnet

Maximum current : 16 A

Maximum input current per phase : 16 A

Maximum power : 3700 W

Monitoring : Current

|  |
|--|
| Mounting : Horizontal  |
| Nominal input voltage : 230 V  |
| Nominal output voltage : 230 V   |
| Operating temperature (T-T) : 0 - 60 °C  |
| Output connections : 8 x C13   |
| Package weight : 3.8 kg  |
| PDU types : Metered  |
| Power plug : C20 coupler   |
| Product colour : Black   |
| Rack capacity : 1U   |
| Rack mount kit : Y   |
| Rack mounting : Y  |
| Supported network protocols : HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS |
| Sustainability certificates : RoHS   |
| Weight : 2.6 kg  |
| Width : 203 mm   |