

HANWHA- Camera QNO-6012R1



DESCRIPTION

- Maximum 2megapixel (1920 x 1080) resolution
- 0.03Lux (Color), 0Lux (B/W, IR LED on)
- 2.8mm fixed lens
- Maximum 30fps@2MP all resolutions (H.265/H.264)
- H.265, H.264, MJPEG codec supported, Multiple streaming
- Motion detection, Tampering, Defocus detection
- Hallway view (90°/270°), LDC support
- Micro SD/SDHC/SDXC memory slot (Maximum 128GB)
- IR viewable length 20m
- IP66, IK10, PoE, 12VDC

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : QNO-6012R1

Représentation / réalisation :

Type : IP security camera

Alarm input channels : 1

Alarm input/output : Y

Alarm output channels : 1

Anti-flicker : Y

Built-in HDD : N

Camera pan control : N

Camera shutter speed : 1/5 - 1/120000 s

Camera shutter type : Electronic

Camera tilt control : N

Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC

Connectivity technology : Wired

DC output voltage : 12

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Fixed focal length (panoramic camera) : 2.8 mm
Fixed focus : Y
Flash memory : 256 MB
Form factor : Bullet
Gain control type : Manual
IK code : IK10
Internal memory : 512 MB
International Protection (IP) code : IP66
Lens viewing angle, diagonal : 134.5°
Lens viewing angle, horizontal : 113.7°
Lens viewing angle, vertical : 61.5°
Maximum aperture number (panoramic camera) : 2
Maximum memory card size : 128 GB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.03 lx
Mounting type : Ceiling/Desktop
Night vision : Y
Noise reduction : Y
Number of cameras : 1
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Indoor & outdoor
Power source type : DC, PoE
Product colour : Black
PTZ control : N
Sensor type : CMOS
Total megapixels : 2 MP
Video formats supported : H.264, H.265
Wide Dynamic Range (WDR) : Y