

Tp-link archer MR200 4G lte modem wireless AC750



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : ARCHER MR200
Sécurité :
Stateful Packet Inspection (SPI) : Y
Réseaux mobiles :
3G : Y
4G : Y
Connexion WAN :
Ethernet WAN : Y
DSL WAN : N
Caractéristiques :
Certification : CE, FCC, RoHS
2G standards : Edge, GPRS, GSM
3G standards : DC-HSPA+, HSPA, HSPA+, UMTS
3G/4G USB modem compatibility : N
4G bands supported : 800,900,1800,2100,2600 MHz
4G standard : LTE
AC adapter included : Y
Antenna design : External
Antennas quantity : 5
Cables included : LAN (RJ-45)
Cabling technology : 10/100Base-T(X)
Data link protocols : IPv4, IPv6
DC-in jack : Y
Depth : 141 mm
Detachable antenna(s) : Y
DHCP client : Y

DHCP server : Y
DoS attack prevention : Y
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 4
Ethernet LAN data rates : 10,100 Mbit/s
Ethernet LAN interface type : Fast Ethernet
Filtering : Y
Firewall : Y
GSM bands supported : 850,900,1800,1900 MHz
Height : 33.6 mm
IP address filtering : Y
Linux operating systems supported : Y
MAC address filtering : Y
Mac operating systems supported : Y
Memory card slot(s) : N
Micro to standard SIM card adapter : Y
Mobile network generation : 4G
Nano to standard SIM card adapter : Y
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
On/off switch : Y
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Output current : 1 A
Output voltage : 12 V
Power source type : AC
Product colour : Black
Product type : Tabletop router
Quality of Service (QoS) support : Y
Quick start guide : Y
Receiver sensitivity : 5GHz: 11a 54M: -74dBm 11ac HT20: -67dBm 11ac HT40: -64dBm 11ac HT80 : -60dBm 11n HT20: -71dBm 11n HT40: -70dBm 2.4G: 11g 54M: -76dBm 11n HT20: -73dBm 11n HT40: -67dBm
Reset button : Y
Security algorithms : 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
SIM card slot : Y
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Top Wi-Fi standard : Wi-Fi 5 (802.11ac)
UMTS bands supported : 900,2100 MHz
Universal Plug and Play (UPnP) : Y
USB port : N
VPN support : PPTP, L2TP, IPSec
Web-based management : Y
Width : 202 mm
Wi-Fi band : Dual-band (2.4 GHz / 5 GHz)
Wi-Fi standards : 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Windows operating systems supported : Y
WLAN data transfer rate (first band) : 300 Mbit/s
WLAN data transfer rate (max) : 433 Mbit/s
WLAN data transfer rate (second band) : 433 Mbit/s
WPS push button : Y