

Eaton 9SX 3000i



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 9SX3000I
Design :
Certification : IEC/EN 62040-1, UL 1778, CSA 22.2, IEC/EN 62040 -2 , FCC Class B, CISPR22 Class B, CE /CB report (TUV) / cULus / EAC / RCM / BIS / KCC
AC outlet types : C13 coupler, C19 coupler
AC outlets quantity : 9 AC outlet(s)
Automatic battery test : Y
Battery technology : Sealed Lead Acid (VRLA)
Bundled software : Intelligent Power Software suite
Depth : 412 mm
Display type : LCD
ECO mode : N
Form factor : Tower
Harmonized System (HS) code : 85078000
Height : 346 mm
Hot-swap battery : Y
Input connection type : IEC C20
Input frequency : 40/70 Hz
Input operation voltage (max) : 276 V
Input operation voltage (min) : 200 V
Management card included : N
Noise level : 45 dB
Nominal input voltage : 230 V
Nominal output voltage : 230 V
Number of input phases : 1
Number of output phases : 1
Operating temperature (T-T) : 0 - 40 °C

Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 2700 W
Output power capacity : 3 kVA
Power factor : 0.9
Power plug : C20 coupler
Product colour : Black
RS-232 ports : 1
Safety : IEC/EN 62040-1, UL 1778, CSA 22.2
Serial interface : Y
Serial interface type : RS-232
Typical backup time at half load : 15.5 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Pure sine
Weight : 33.4 kg
Width : 214 mm