

Wireless AC1300 ap ceiling mount poe+



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ENGЕНИUS
Part number : ECW260
Caractéristiques :
5 GHz : Yes
6 GHz : No
BeamForming : Yes
Design :
Certification : FCC, CE, IC
2:4 GHz : Yes
Antenna connector type : SMA
Antenna direction type : Omni-directional
Antenna features : Detachable antenna
Antenna gain level (max) : 5 dBi
Antenna included : Yes
Antenna type : External
Antennas quantity : 4
Built-in processor : Yes
Depth : 190 mm
Ethernet LAN (RJ-45) ports : 1
Ethernet LAN data rates : 10,100,1000,2500 Mbit/s
Height : 52.5 mm
International Protection (IP) code : IP67
LED indicators : LAN, Power, WLAN
MAC address filtering : Yes
Maximum data transfer rate : 1774 Mbit/s
Maximum data transfer rate (2:4 GHz) : 574 Mbit/s
Maximum data transfer rate (5 GHz) : 1200 Mbit/s

MIMO : Yes
MIMO type : Multi User MIMO
Mounting kit : Yes
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11e, IEEE 802.11g, IEEE 802.11n, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3af, IEEE 802.3at
Number of products included : 1 pc(s)
Number of SSID supported : 8
Operating temperature (T-T) : -20 - 60 °C
Package depth : 284 mm
Package height : 144 mm
Package weight : 1.8 kg
Package width : 234 mm
Placement : Pole, Wall
Power consumption (max) : 15.9 W
Power over Ethernet (PoE) : Yes
Power over Ethernet (PoE) type supported : Active PoE
Processor frequency : 1800 MHz
Processor model : ARM Cortex-A53
Product colour : White
Quality of Service (QoS) support : Yes
Quick start guide : Yes
Security algorithms : SNMP, SNMPv2, SNMPv3, WPA2-AES, WPA2-Enterprise, WPA3-Enterprise, WPA3-PSK
Service Set Identifier (SSID) features : Hidden SSID, Multiple SSIDs
Spread spectrum method : DSSS
Storage temperature (T-T) : -40 - 80 °C
Virtual LAN features : Tagged VLAN
VLAN support : Yes
Weight : 700 g
Width : 124 mm
Wi-Fi Multimedia (WMM)/(WME) : Yes