

BOSCH- Camera NBE-5703-AL



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BOSCH
Part number : NBE-5703-AL
Représentation / réalisation :
Type : IP security camera
Certification : CE, FCC, UL, WEEE, RCM, VCCI, UKCA, China RoHS, BIS
AC input voltage : 24 V
Alarm input/output : Yes
Audio detection : Yes
Card reader integrated : Yes
Compatible memory cards : MicroSDHC, MicroSDXC
Connectivity technology : Wired
Country of origin : Thailand
Day/night mode : Yes
Diameter : 14.8 cm
Doesn't contain : PVC
Dynamic range : 120 dB
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Flash memory : 8192 MB
Form factor : Bullet
Frame rate : 30 fps
Height : 97 mm
Housing material : Aluminium, Plastic
IK code : IK10
Infra-red wavelength : 850 nm
International Protection (IP) code : IP66, IP67
LED type : IR

Lens diameter : 1.05 cm
Lens viewing angle, horizontal : 96 - 29°
Lens viewing angle, vertical : 71 - 2°
Manual : Yes
Maximum memory card size : 2 TB
Maximum resolution : 2592 x 1944 pixels
Microphone in : Yes
Mirror : Yes
Mounting kit : Yes
Mounting type : Ceiling
Networking standards : IEEE 802.3af, IEEE 802.3at
Night vision : Yes
Night vision distance : 60 m
Number of cameras : 1
Number of effective pixels (H x V) : 2688 x 1944 pixels
Number of lenses : 1
Number of Privacy masking areas : 8
Operating relative humidity (H-H) : 5 - 93%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 2.7 mm (1 / 2.7»)
Placement supported : Outdoor
Power consumption (max) : 10.86 W
Power consumption (typical) : 6.42 W
Power source type : AC, PoE, DC
Product colour : White
Protection features : Impact resistant
RAM capacity : 2048 MB
Screws included : Yes
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage relative humidity (H-H) : 0 - 98%
Storage temperature (T-T) : -30 - 70 °C
Supported network protocols : IPv4; IPv6; UDP; TCP; HTTP; HTTPS; RTP/RTCP; IGMP V2/V3; ICMP; ICMPv6; RTSP; FTP; ARP; DHCP; APIPA (Auto-IP, link local address); NTP (SNTP); SNMP (V1, MIBII); SNMP (V3, MIBII); 802.1x, EAP/TLS; DNS; DNSv6; DDNS (DynDNS.org, selfHOST.de, noip.com); SMTP; iSCSI; UPnP (SSDP); DiffServ (QoS); LLDP; SOAP; CHAP; Digest authentication; SCEP
Supported video modes : 1080p, 480p, 720p
Total megapixels : 5 MP
USB port : Yes
Video formats supported : H.264, M-JPEG, H.265, HEVC
Video streaming : Yes
Weight : 2.5 kg
Wide Dynamic Range (WDR) : Yes
Zoom capability : Yes