# Ambergrease FG1

## **Technical Data**

**AMBERGREASE FG1** is designed to cover a wide range of food grade applications, encompassing extremes of temperature, wet and saturated environments, heavily loaded applications and where there is a presence of dust and other contaminants. Ambergrease FG1 grease contains Extreme Pressure (EP) additives and PTFE to provide a high degree of anti-wear performance. All ingredients are FDA listed. Suitable for all plain and anti-friction bearings as well as sliding surfaces.

## **COST SAVING BENEFITS**

- 1. Wide performance characteristics enable standardisation to one product for most 'food grade' applications
- 2. Extends lubrication intervals
- 3. Excellent anti-wear performance prolonging component life
- 4. Exceptional degree of water resistance providing lasting lubrication and protecting against corrosion

### METHOD OF APPLICATION

Ambergrease FG1 can be applied by hand, or by using a standard grease gun

### TECHNICAL DATA

:	H1
:	138264
:	White tacky grease
:	2
:	Aluminium complex
:	> 230°C
:	Polyalphaolefin
:	47 cSt
:	0.5%
:	White lubricating solids and PTFE
:	Negative
:	< 1% max.
:	0:0
:	200kg
:	400,000
:	-50°C to +165°C
:	400g cartridge, 18kg pail





# **PART NUMBER:** 615009370







All ingredients are FDA listed. **Ambergrease FG1** is NSF H1 registered and meets the USDA 1998 H1 Guidelines (This product contains no genetically modified ingredients). Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives.

#### STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 36 months with correct storage. Aerosols should always be stored below  $50^{\circ}$ C, away from direct heat and naked flame.

#### **HEALTH AND SAFETY**

Health and Safety sheet available separately.

#### MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.