

EV-SERIES




Shown from left to right:
EV-43M4, EV-11, EV-52H3, EV-23

EV-SERIES HYDRAULIC VALVES

EAGLE PRO hydraulic valves are available for most of your applications. EAGLE PRO hydraulic valves are available with a manual control, solenoid directional control and flow control valves. EAGLE PRO hydraulic valves are designed and manufactured for safe operation up to 10,000 PSI.




EV-11



Needle valve, manually control the speed of cylinder, can be used as shut-off valve for temporary load holding.











EV-23



Manually Operated Check Valve. used to hold load with single or double acting cylinder, manually opened to allow oil to flow back to oil reserve when cylinder retracts

EV-SERIES

DIRECTIONAL CONTROL VALVES

Used with cylinder	Valve Operation	Valve Location	Model	Valve Type	Valve Function	Hydraulic Symbol	Weight (lbs)
Single Acting	Manual	Pump Mounted	EV-42H2	2 Position	Advance Return		4.4
	Manual	Pump Mounted	EV-43M3	3 Position	Advance Hold/Return		2.86
	Manual	Remote Mounted	EV-43M3L	3 Position	Advance Hold/Return		4.84
	Manual	Pump Mounted	EV-43M3T	3 Position	Advance Hold/Return		8.36
	Manual	Remote Mounted	EV-43M3LT	3 Position	Advance Hold/Return		10.34
	Solenoid 24V	Pump Mounted	EV-52H2	2 Position	Advance Return		3.96
	Solenoid 24V	Pump Mounted	EV-52H3	2 Position	Advance Return		3.96
Double Acting	Manual	Pump Mounted	EV-43M4	3 Position	Advance Hold/Return		2.86
	Manual	Remote Mounted	EV-43M4L	3 Position	Advance Hold/Return		4.84
	Manual	Pump Mounted	EV-43M4T	3 Position	Advance Hold/Return		8.36
	Manual	Remote Mounted	EV-43M4LT	3 Position	Advance Hold/Return		10.34
	Solenoid 24V	Pump Mounted	EV-52H4	2 Position	Advance Return		3.96