

High Temperature Swivel Plate Fitting Castors

34 (Pressed Steel Bracket) and GNG Series (Fabricated Bracket)

Pressed or fabricated steel brackets, specialist wheels and double ball race swivel heads make these ranges suitable for use in more extreme internal and external applications.

Rated to temperatures of -40 C to +280 C.

GNG Series Frames and wheels are supplied

GREASE FREE with grease nipples for the user to apply the appropriately rated high temperature grease. Temperature ratings will then be dependent upon the specific grease used.



Wheel Dia. (mm)	Tread Width (mm)	Load Cap. (kg)	Overall Height (mm)	Plate / Bolt Hole Dimensions (mm)		Suits Bolt Dia. (mm)	Wheel Type	Bearing Type	Swivel Radius (mm)	Catalogue Reference		
				Plate	Bolt Ctrs					Swivel	Braked	Fixed
34 Series Top Plate Fitting												
80	35	100	108	Swivel 105 x 85 Fixed 103 x 85	80/77 x 60	9	Phenolic Resin	Plain	84.5	3470BOO080P62	3477BOO080P62	3478BOO080P62
100	35	125	128	Swivel 105 x 85 Fixed 103 x 85	80/77 x 60	9	Phenolic Resin	Plain	91	3470BOO100P62	3477BOO100P62	3478BOO100P62
125	35	150	155	Swivel 105 x 85 Fixed 103 x 85	80/77 x 60	9	Phenolic Resin	Plain	102.5	3470BOO125P62	3477BOO125P62	3478BOO125P62
160	50	250	200	Swivel 137 x 105 Fixed 137 x 115	105 x 80	11	Phenolic Resin	Plain	135	3470BOO160P63	3477BOO160P63	3478BOO160P63
200	50	300	240	Swivel 137 x 105 Fixed 137 x 115	105 x 80	11	Phenolic Resin	Plain	135	3470BOO200P63	3477BOO200P63	3478BOO200P63
34 Series Bolt Hole Fitting												
80	35	100	108	-	-	13	Phenolic Resin	Plain	84.5	3470BOO080P30	3477BOO080P30	n/a
100	35	150	128	-	-	13	Phenolic Resin	Plain	91	3470BOO100P30	3477BOO100P30	n/a
125	40	200	155	-	-	13	Phenolic Resin	Plain	102.5	3470BOO125P30	3477BOO125P30	n/a
GNG Series Top Plate Fitting (Fabricated Bracket)												
100	45	320	142	130 X 105	105 x 80/75	10	Cast Iron	Plain	89	TSG100CI0GNG	n/a	TFG100CI0GNG
150	45	450	189	130 X 105	105 x 80/75	10	Cast Iron	Plain	124	TSG150CI0GNG	n/a	TFG150CI0GNG