

# PVC Lane Marking Adhesive Tape




## PVC Tape

### Description

Scapa 2721 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubber based

Adhesive system. It combines excellent mechanical strength, easy transversal tear ability and abrasion

Resistance with excellent conformability for use in lane marking and flooring applications



### Applications

- Colour coding
- Flooring and lane marking
- General splicing

### Product Benefits

- Excellent resistance to abrasion, corrosion and moisture
- Suitable for indoor and protected outdoor environments
- Excellent conformability
- Easy transversal tear ability
- Environmentally friendly technology
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)

Technical Properties	Unit	Value	Test Method
Nominal Thickness	mm	0.16	CEI EN 60454
Tensile Strength	N/cm	25	CEI EN 60454
Elongation at Break	%	150	CEI EN 60454
Adhesion to Steel	N/cm	1.5	CEI EN 60454
Adhesion to Backing	N/cm	1.5	CEI EN 60454

### Standard Presentation

Roll length: 33 metres

Roll width: 50, 75 and 100mm

Core: 76mm Scapa branded cardboard core

Packaging: Heat shrink sleeve

Colours: Black, Yellow, White, Red, Blue, Light green

### Recommendations

Rolls should be stored \_at on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Use within 24 months of receipt.

The tape should be applied with sufficient pressure to ensure an optimum bonding and prevent \_flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.