


NEO 390 2



Neoprene hose, double-layer, leak-proof (up to +150°C)

Applications

- flexible hose/ ducting for hot and cold gases
- granulate/ plastic dryer, hot air dryer
- film blowing machine, cooling air at the extrusion tool
- air supply: UV dryer, IR dryer
- bus, utility vehicle, caravan/ trailer, mobile home/ camper/ RV, boat, ship/ vessel/ marine, yacht: ventilation, heating

Properties

- fibre reinforced
- very good heat resistance
- conforms to RoHS guideline

Temperature Range

- 35°C to 135°C
- short time to 150°C

Design, Material

Neoprene hose

- spring steel wire integrated in wall
- fabric-reinforced tape; wall: Neopren coated glass fabric
- cord as reinforcement

Delivery variants

- further diameters and lengths available on request

I.D. in / mm	O.D. mm	Over- pressure bar	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Further Production Lengths m	Order No.
- / 13	16	3,000	0,740	10	0,070	-	4	390-0013-2005
3/4 / 19	22	3,000	0,730	13	0,110	4	-	390-0019-2005
- / 22	25	3,000	0,720	14	0,170	4	-	390-0022-2005
1 / 25	30	2,800	0,710	18	0,190	4	-	390-0025-2005
1,25 / 32	36	2,700	0,650	20	0,280	4	-	390-0032-2005
1,5 / 38	43	2,600	0,600	24	0,310	4	-	390-0038-2005
- / 41	46	2,600	0,590	26	0,315	-	4	390-0041-2005
1,75 / 44-45	49	2,600	0,580	27	0,320	4	-	390-0044-2005
2 / 50-51	56	2,600	0,520	31	0,360	4	-	390-0051-2005
2,25 / 57	62	2,500	0,480	34	0,430	4	-	390-0057-2005
2,5 / 63-65	68	2,400	0,460	37	0,490	4	-	390-0063-2005
- / 70	75	2,100	0,440	40	0,540	4	-	390-0070-2005
3 / 75-76	81	2,100	0,430	43	0,580	4	-	390-0076-2005
- / 80	85	2,100	0,420	45	0,610	4	-	390-0080-2005
3,2 / 83	88	2,100	0,410	47	0,630	4	-	390-0083-2005
3,5 / 89-90	94	2,000	0,400	50	0,690	4	-	390-0089-2005
- / 95	100	1,900	0,370	53	0,730	4	-	390-0095-2005
4 / 100-102	107	1,900	0,350	56	0,770	4	-	390-0102-2005
- / 108	114	1,800	0,330	60	0,810	4	-	390-0108-2005
4,5 / 114	120	1,500	0,300	63	0,850	4	-	390-0114-2005
- / 121	127	1,500	0,240	67	0,890	4	-	390-0121-2005
5 / 125-127	133	1,400	0,230	70	0,930	4	-	390-0127-2005
5,5 / 140	146	1,300	0,200	76	1,000	4	-	390-0140-2005
6 / 150-152	158	1,200	0,170	82	1,200	4	-	390-0152-2005
6,3 / 160	166	1,100	0,160	86	1,280	-	4	390-0160-2005
6,5 / 165	171	1,100	0,140	89	1,380	-	4	390-0165-2005
7 / 178-180	184	1,000	0,120	95	1,430	4	-	390-0178-2005
8 / 200-203	209	0,700	0,090	108	1,650	4	-	390-0203-2005
10 / 254	260	0,500	0,070	133	2,090	4	-	390-0254-2005
12 / 305	311	0,500	0,070	159	2,610	4	-	390-0305-2005

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.

Additional technical data at www.norres.com/en/technology. Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.


Accessories



CLAMP 208



CLAMP 211



CONNECT 228



CONNECT 270-271