

# Floor Paint



## Description

Floor Paint is a single pack polyurethane formulation and will dust-proof, seal and transform drab concrete floors.

## Main Properties

Easy to apply. Dries quickly to a tough finish, no primer required. Available in 10 colours. Easy to clean.

## Recommended Uses

Product is suitable for general industrial use.

### Also available:

Floor Paint Slip-Resistant Grade and Floor Paint Epoxy Ester Grade. We recommend Epoxy Floor Paint for very heavy wear areas.

## Technical Data

Appearance:	Mid gloss finish
Colours:	Buff, terracotta, tile red, mid blue, mid green, mid grey, light grey, dark grey, white, yellow
Drying Times	20°C/50% r.h.
To recoat:	12 hours (over-coating or light foot traffic)
Full hardness:	Ensure the paint is hard dry (not just touch dry) before bringing the area back into use.
Coverage	
Theoretical:	Up to 4m <sup>2</sup> per litre allowing for two coats. Application by brush will result in reduced coverage.
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## Surface Preparation

The concrete should be clean, dry and free from any loose material, and sufficiently porous to allow the paint to penetrate into the surface. Previously painted surfaces should be roughened slightly.

If the concrete is new it should be left for at least 28 days and the surface then treated with Cement Cleaner/Etchant to neutralise any remaining alkalinity from the cement. If there is surface laitance (a soft, easily crumbled skin) on the concrete, or if it is suspected that a chemical hardener has been used or if the bare surface of the concrete is particularly smooth, treat with Cement Cleaner/Etchant and paint a trial area first to test adhesion and cure.

Grease and oil should be removed with a solvent-free degreaser and the surface left to dry thoroughly before painting.



## Directions for Use

The paint must always be stirred very thoroughly and any thicker bottom deposit blended in.

## Application & Thinning

The paint must always be stirred very thoroughly and any thicker bottom deposit blended in. The paint must not be thinned. Apply by pile-type roller and work well into the surface. Avoid applying the paint too thickly. Apply the second coat as soon as the first is dry.

## Remarks

Floor Paint will resist oil spillages and the normal range of neutral cleaners. Stronger degreasers should be tested first. Do not apply to asphalt, PVC, thermoplastic tiles, latex levelling compounds or to surfaces subject to rising damp. General cleaning should be carried out with a neutral cleaner. The painted floor should not be cleaned with strong solvents or caustic detergents.

### Exterior Use:

The product can be applied outside. Please ensure surfaces are clean, dry and free of loose material and contamination. In common with most floor paints there may be some dulling or discolouration over a period of time, depending on the level of exposure to sunlight. Delamination may occur if used on surfaces subject to rising damp. Protect paint from rain and excessive moisture until paint has fully dried, usually 8-16 hours in dry, warm (above 150°C) well ventilated conditions. SuperGrip Treadsafe, a coarse, gritty epoxy resin coating, is recommended for areas which may become very wet and slippery.

## Safety

Consult Safety Data Sheet and Safety Information printed on the can. Food products must be removed from the area during application and cure.

## Shelf Life / Storage Conditions

Keep at normal ambient temperature in a dry place.