


TIMBERDUC® PUR 532 SE AS



Antistatic polyurethane hose for the woodworking industry, medium-heavy, flame-retardant

Applications

- extraction unit, dedusting system, filter system, oil mist extraction
- explosion hazard area
- wood dust extraction, wood chips: furniture production, saw mill
- wood dust extraction: vertical panel saw, saw, woodworking machine, edge processing machine, parquet flooring grinding machine

Properties

- medium-heavy duty
- highly flexible + compressible 3:1
- abrasion-resistant
- microbe resistant
- good resistance to oil, gasoline and chemicals
- flame-retardant according to: DIN 4102-B1

- permanently antistatic wall: electrical and surface resistance $<10^9 \Omega$
- in accordance with ATEX 2014/34/EU and German TRGS 727: pneumatic transport of flammable dusts and bulk materials (Zone 20, 21, 22 inside), aspiration of combustible dusts (Zone 22 inside), for conveying for flammable liquids (inside zone 0, 1, 2), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in zone 0 (gases)
- conforms to the safety regulations of the German Wood Trade Association
- conforms to RoHS guideline

Temperature Range

- -40°C to 90°C
- short time to 125°C

Design, Material

patented PROTAPE® tape hose

1. spring steel wire integrated in wall
2. wall: permanently antistatic premium polyurethane (Pre-PUR®), resistant to aggressive wood types and wood preservatives
3. wall thickness 0,6 mm approx.

Delivery variants

- further diameters and lengths available on request
- transparent + partially silver coloured (standard)
- special colours: partially coloured, completely coloured
- customer-specific branding

I.D. in / mm	O.D. mm	Over- pressure bar	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Order No.
- / 40	47	1,020	0,335	27	0,260	5 10 15	532-0040-0000
1,75 / 44-45	52	0,910	0,300	30	0,290	5 10 15	532-0045-0000
2 / 50-51	58	0,820	0,220	33	0,360	5 10 15	532-0050-0000
- / 55	63	0,755	0,200	36	0,390	5 10 15	532-0055-0000
2,36 / 60	68	0,685	0,180	38	0,430	5 10 15	532-0060-0000
2,5 / 63-65	73	0,635	0,165	41	0,470	5 10 15	532-0065-0000
- / 70	78	0,590	0,155	43	0,500	5 10 15	532-0070-0000
3 / 75-76	83	0,550	0,145	46	0,530	5 10 15	532-0075-0000
- / 80	88	0,515	0,135	48	0,570	5 10 15	532-0080-0000
3,5 / 89-90	98	0,460	0,120	53	0,630	5 10 15	532-0090-0000
4 / 100-102	108	0,415	0,080	58	0,660	5 10 15	532-0100-0000
- / 110	118	0,375	0,070	63	0,730	5 10 15	532-0110-0000
4,72 / 120	128	0,345	0,065	68	0,790	5 10 15	532-0120-0000
5 / 125-127	133	0,335	0,065	71	0,820	5 10 15	532-0125-0000
- / 130	138	0,320	0,060	73	0,850	5 10 15	532-0130-0000
5,5 / 140	148	0,295	0,055	78	0,920	5 10 15	532-0140-0000
6 / 150-152	158	0,275	0,055	83	0,980	5 10 15	532-0150-0000
6,3 / 160	168	0,260	0,050	88	1,040	5 10 15	532-0160-0000
7 / 178-180	188	0,230	0,045	98	1,170	5 10 15	532-0180-0000
8 / 200-203	208	0,210	0,030	108	1,540	5 10 15	532-0200-0000
- / 225	233	0,185	0,025	121	1,750	5 10	532-0225-0000
- / 250	258	0,165	0,025	133	1,900	5 10 15	532-0250-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.

I.D. in / mm	O.D. mm	Over- pressure bar	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Order No.
11 / 280	288	0,150	0,020	148	2,150	5 10	532-0280-0000
- / 300	309	0,140	0,020	159	2,530	5 10	532-0300-0000
- / 315	324	0,135	0,020	167	2,650	5 10	532-0315-0000
- / 350	359	0,120	0,020	184	2,950	5 10	532-0350-0000
- / 400	409	0,105	0,015	209	3,360	5 10	532-0400-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional technical data at www.norres.com/en/technology/

Accessories




CLAMP 212



CLAMP 217



CLAMP 213



CONNECT 228



CONNECT 223



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.