

# O-Ring Splicing Kit

## Contents:

### Rubber Cord

Consists of the following sizes (2mtrs of each)

1.78mm, 2mm, 2.4mm, 2.62mm, 3mm,  
3.53mm, 4mm, 4.5mm, 5mm, 5.33mm,  
5.7mm, 6mm, 7mm, 8mm.

1 Tape Measure

1 Cutting Block (For Butt or Scarf Joins)

1 Cutting Knife

1 Tube of Glue

(The glue is very strong and effective, avoid contact with skin, eyes etc. At all times)

When using the glue, always ensure you prick the opening with the enclosed pin before each use. This will enable you to spread the glue more evenly.

N.B Both the glue and cord are able to stand temperatures ranging between -20°C to +100°C.

## Material:

Nitrile

## Making an O-Ring:

Once you have obtained the required length of cord, use the knife and cutting block to cut the cord. Ensure the cut is smooth and free from oil, grease and dust. Spread a thin layer of glue on one of the ends, and using the ridge of the cutting block, unite the two ends, holding the ends in the ridge, press firmly together for 20-30 seconds. Then leave to dry for about 2-3 minutes. The O-Ring should now be ready for use.



Ideal for repairing or replacing damaged O-Ring seals.

PART CODE

SPLICING-KIT01