

ElectroLuber™



Technical Spec

Installation	single-point
Type	electrochemical
Pressure	0-4 bar
Temperature	-40°C to 55°C
Remote mounting	Up to 1m
Dispense cycle	15 days to 12 months
Capacity	60, 125, 250, 475ml
Refill	No
Power	Battery
Lubricant	Grease or oil



Competition

- SKF System 24
- Perma Classic
- Simalube
- Pulsarlube E
- Greasomatic

Retail Advantages

1. Most reliable lubricator on the market by a huge distance fail rate <0.01% vs 20% in some competitors
2. Widest temperature range of any electrochemical unit food / beverage / pharmaceutical / agriculture / rail
3. submersible to 10m rail / agriculture / water treatment / hydro
4. ATEX certified for explosive & underground zones pulp & paper / metro / mining / oil & gas / flour / cement
5. remote mount to 1000mm improved safety of operatives, away from steam etc
6. fill with any brand of lubricant

Industry Advantages

- Incredibly versatile: use in wet zones, ATEX zones, extreme temperature
- Continuous, precise lubrication for constantly moving components & heavy workloads
- Reduce bearing failure by up to 80%
- Significantly reduce maintenance hours: some clients save 40+ hours per week
- Extend machinery service life and minimise downtime

All ATS ElectroLube units are guaranteed for 1 year