



SERIE 025S.08

PNEUMATIC COUPLINGS  
PNEUMATISCHE KUPPLUNGEN



SAFETY COUPLING WITH PUSH BUTTON  
SICHERHEITSKUPPLUNG MIT DRUCKKNOPF

**Interchangeability - Kompatibilität**  
TST 026, RECTUS 25, RECTUS 26, CEJN 320,  
PARKER PEF, JWL 520, JWL 530, Legris

**Temperature Range - Temperaturbereich**  
-20 °C +100 °C (-4 °F +212 °F)


**Working Pressure - Betriebsdruck**  
0 - 12 bar (0 - 508 PSI)

**Flow capacity - Nennweite**  
NW - 7.4

For optional orders please add the symbol  
of your option end of the order no.  
Bei Bestellungen Kennbuchstabe  
bitte hinzufügen.


**Material -Material**

- Inner Part - Innenteil : Aluminium - Eloxal -  
Aluminium - Eloxal
- Back Part - Verschluss : Brass Nickel Plated -  
Messing Vernickelt
- Valve - Ventil : Steel Chrome Plated  
Stahl Verchromt
- Spring - Feder : Stainless Steel -  
Edelstahl
- Coupler Body - Gehäuse : Steel Chrome Plated  
Stahl Verchromt
- Seals - Dichtungen : Nitrile (Ni) - NBR
- Balls - Kugeln : AISI 420 Hardened  
Edelstahl AISI 420
- Push Button -  
Druckknopf : AISI 420 Hardened Steel  
Chrome Plated -  
Edelstahl AISI 420  
Verchromt




**Couplers and Plugs  
Kupplungen und Nippel**

Connection Anschlüsse	Order No Bestellnr.	SW	L	ØD
--------------------------	------------------------	----	---	----




Male Thread Coupling  
Kupplung mit Aussengewinde

BSP 1/4"	025.S08 EG 13	20	69.3	26
BSP 3/8"	025.S08 EG 17	20	68.3	26
BSP 1/2"	025.S08 EG 21	25	70.3	26



Female Thread Coupling  
Kupplung mit Innengewinde

BSP 1/4"	025.S08 DG 13	20	69.6	26
BSP 3/8"	025.S08 DG 17	20	72.3	26
BSP 1/2"	025.S08 DG 21	24	74.3	26



Standard hose Barb Coupling  
Kupplung mit Schlauchtülle

Ø 6 - 1/4"	025.S08 HG 06	20	83.6	26
Ø 8 - 5/16"	025.S08 HG 08	20	83.6	26
Ø 10 - 3/8"	025.S08 HG 10	20	83.6	26