


EVA 373



Vacuum cleaner hose

Applications

- flexible hose/ ducting for gases and for dust, powder, fibres
- industrial vacuum cleaners, vacuum cleaners
- swimming pool cleaning
- scrubber, floor cleaning machine

- light weight
- highly flexible
- crush resistant
- floatable
- good resistance to alkalis and acids
- conforms to RoHS guideline

Design, Material

EVA design

- self-supporting profile design
- open profile geometry; wall: EVA

Delivery variants

- further diameters and lengths available on request
- grey (standard)

Properties

Temperature Range

- 45°C to 65°C

I.D. in / mm	O.D. mm	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Further Production Lengths m	Order No.
- / 20	26,8	0,500	42	0,130	-	30	373-0020-0000
1 / 25	32,2	0,500	54	0,150	-	30	373-0025-0000
- / 30	38,0	0,500	62	0,200	-	30	373-0030-0000
1,25 / 32	40,4	0,500	66	0,240	30	-	373-0032-0000
1,36 / 35	43,8	0,500	71	0,260	-	30	373-0035-0000
1,5 / 38	47,2	0,500	74	0,310	30	-	373-0038-0000
- / 40	49,4	0,500	80	0,320	-	30	373-0040-0000
1,75 / 44-45	55,0	0,500	89	0,370	30	-	373-0045-0000
2 / 50-51	60,4	0,500	97	0,440	30	-	373-0050-0000
2,36 / 60	72,0	0,500	113	0,670	-	30	373-0060-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional technical data at www.norres.com/en/technology/

Accessories



CLAMP 208



CONNECT 228



CONNECT 227

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.