



## 92 Elbow 90°, equal, ISO/EN A4

EN		Dim. [inch]	Code	a [mm]	b [mm]	z [mm]	
•	B	1/8	770 092 101	19	25	12	
•	G	1/8	770 092 201	19	25	12	
•	B	1/4	770 092 102	21	28	11	
•	G	1/4	770 092 202	21	28	11	
•	B	3/8	770 092 103	25	32	15	
•	G	3/8	770 092 203	25	32	15	
•	B	1/2	770 092 104	28	37	15	
•	G	1/2	770 092 204	28	37	15	
•	B	5/8	770 092 105	33	43	18	
•	G	5/8	770 092 205	33	43	18	
•	B	1	770 092 106	38	52	21	
•	G	1	770 092 206	38	52	21	
•	B	1 1/4	770 092 107	45	60	26	
•	G	1 1/4	770 092 207	45	60	26	
•	B	1 1/2	770 092 108	50	65	31	
•	G	1 1/2	770 092 208	50	65	31	
•	B	2	770 092 109	58	74	34	
•	G	2	770 092 209	58	74	34	
•	B	2 1/2	770 092 110	69	88	42	
•	G	2 1/2	770 092 210	69	88	42	
•	B	3	770 092 111	78	98	48	
•	G	3	770 092 211	78	98	48	
•	B	4	770 092 112	96	118	60	
•	G	4	770 092 212	96	118	60	



## 92 Elbow 90°, male thread reduced, ISO/EN A4

EN		Dim. (1-2) [inch]	Code	a [mm]	c [mm]	z1 [mm]	
•	B	1/2 - 3/8	770 092 116	26	33	13	
•	G	1/2 - 3/8	770 092 216	26	33	13	
•	B	3/4 - 1/2	770 092 117	30	40	15	
•	G	3/4 - 1/2	770 092 217	30	40	15	
•	B	1 - 1/2	770 092 130	32	46	15	
•	G	1 - 1/2	770 092 230	32	46	15	
•	B	1 - 3/4	770 092 118	35	46	18	
•	G	1 - 3/4	770 092 218	35	46	18	
-	G	1 1/4 - 3/4	770 092 219	44	51	17	
•	B	1 1/4 - 1	770 092 120	40	56	21	
•	G	1 1/4 - 1	770 092 220	40	56	21	
-	B	1 1/2 - 1	770 092 121	47	62	28	
-	G	1 1/2 - 1	770 092 221	47	62	28	
-	B	1 1/2 - 1 1/4	770 092 122	52	64	33	
-	G	1 1/2 - 1 1/4	770 092 222	52	64	33	