Amberklene FE10

ambers in making the difference


Technical Data



AMBERKLENE FE10 is a fast evaporating solvent blend which contains no CFCs or other chlorinated solvents. It is an ideal alternative to 1,1,1 Trichloroethane.

Textiles

APPLICATIONS



- Office Equipment
 PCBs and Electronics
- MouldingAutomotiveOffshore
- Printing Agriculture Aviation
- MarineElectric Motors
- Light and Heavy Engineering

Efficiently cleans plastics, ferrous and non-ferrous metals, evaporating quickly to leave a clean, dry surface. Also recommended for spot removal in the textiles and associated industries.

N.B. May affect certain plastics. Always test a small, inconspicuous area before general use. Ensure electrical equipment is switched off before cleaning.

TECHNICAL DATA

Appearance : Clear, colourless liquid

Odour : Mild and sweet

Specifications/Approvals : NATO Catalogue No. 6850-99-6636478

SG @ 25°C : 0.770

Pressure @ 25°C : 5 - 6 Bar

Discharge rate : 2.5 g/sec



PART NUMBER: 6130002500

Kb value : 75

Initial boiling point : 64°C

Freezing point : Below -50°C

Evaporation rate : 6.0 (with respect to Butyl Acetate)

Flammability : Classified as extremely flammable under

Current EC Regulations

Flashpoint -18°C (Bulk)

Packaging : 400 ml aerosol (12 per carton). Also

available in non-aerosol, 1 litre (packed

12 per box), 5 and 25 litres

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

