

# Interchange Range

## Euro Couplings



Specially designed and developed by PCL suitable for most general compressed air applications where this adaptor profile is required.

### Key Product Benefits

- Robust slim line construction
- Single action connection
- Steel construction with corrosive resistant finish
- Built-in swivel prevents hose kinking

### Specifications

Nominal bore	5.5 mm	
Flow rate @ 6bar	650 l/min @ 0.5 bar p.d.	
Maximum Working Pressure	200 lbf/in <sup>2</sup>	14 bar
Interchangeability	Rectus 14	
	Rectus 22	
	ARO 210	
	Schrader Euro	
	JWL 522/532	

### Product Options

Part No.	Description	Thread Type	Thread Size
AC61CM	Euro Coupling	Male	R 1/4
AC61EM	Euro Coupling	Male	R 3/8
AC61JM	Euro Coupling	Male	R 1/2
AC61CF	Euro Coupling	Female	Rp 1/4
AC61EF	Euro Coupling	Female	Rp 3/8
AC61JF	Euro Coupling	Female	Rp 1/2
AC61R	Euro Coupling	Hose Tailpiece	7mm
AC61S	Euro Coupling	Hose Tailpiece	8mm
AC61T	Euro Coupling	Hose Tailpiece	10mm