

Interchange Range

KF Couplings



This range of couplings offers excellent flow characteristics ideal for portable air tool and industrial applications where this adaptor profile is required.

Designed and manufactured in Sheffield by PCL.

Key Product Benefits

- Offers enhanced tool efficiency
- Steel construction with corrosive resistant finish
- Steel shoulder prevents accidental disconnection

Specifications

Nominal bore	7.6 mm	
Flow rate @ 6bar	2100 l/min @ 0.5 bar p.d.	
Maximum Working Pressure	500 lbf/in ²	35 bar
Interchangeability	Rectus 13	
	Nitto Kohki 200	

Product Options

Part No.	Description	Thread Type	Thread Size
AC78CM	KF Coupling	Male	R 1/4
AC78EM	KF Coupling	Male	R 3/8
AC78JM	KF Coupling	Male	R 1/2
AC78CF	KF Coupling	Female	Rp 1/4
AC78EF	KF Coupling	Female	Rp 3/8
AC78JF	KF Coupling	Female	Rp 1/2
AC7806	KF Coupling	Hose Tailpiece	6mm
AC7808	KF Coupling	Hose Tailpiece	8mm
AC7810	KF Coupling	Hose Tailpiece	10mm
AC7813	KF Coupling	Hose Tailpiece	13mm