

RECTUS SERIES 26KP



Brass/Steel Low Pressure Quick Release Couplings, Nominal Diameter 7.4 = 25mm²

Technical Description:

Industrial coupling with high flow performance from UltraFlo technology. Specially suited to use with gaseous media in industry. The steel sleeve counters oscillating forces. Special variant with brass valve for use with liquids.



Working Temperature:
-20°C up to +100°C (NBR)



Working Pressure:
12 bar

Flow Rate:

1.225 l/min

At input pressure 6 bar, pressure drop 0.6 bar



Material:

- Coupling: anodised Aluminium, Brass nickel plated
- Plug: Zinc plated steel
- Seal: NBR

Coupler - Male Thread



C	Part Number
G 1/4	26KPAW13APX
G 3/8	26KPAW17APX
G 1/2	26KPAW21APX

Plug - Male Thread




C	Part Number
R 1/4	25SFAK13SXZ
R 3/8	25SFAK17SXZ
R 1/2	25SFAK21SXZ

Coupler - Female Thread



C	Part Number
G 1/4	26KPIW13APX
G 3/8	26KPIW17APX
G 1/2	26KPIW21APX

Plug - Female Thread



C	Part Number
G 1/4	25SFIW13SXZ
G 3/8	25SFIW17SXZ
G 1/2	25SFIW21SXZ

Coupler - Hose Barb



I.D. Hose	Part Number
6 mm	26KPTF06APX
8 mm	26KPTF08APX
10 mm	26KPTF10APX
13 mm	26KPTF13APX

Plug - Hose Barb



I.D. Hose	Part Number
6 mm	25SFTF06SXZ
8 mm	25SFTF08SXZ
10 mm	25SFTF10SXZ
13 mm	25SFTF13SXZ