

Water

HOZELOCK
TRICOFLEX

Tricoflat PVC

Flat hoses.

Three layer design in PVC with polyester fibre reinforcement. Blue exterior covering for Tricoflat or red for Supertricoflat.

No Marking

Advantages

The polyester fibre reinforcement gives Tricoflat (blue) and Super Tricoflat (red) excellent pressure, tensile and tear resistance. These robust hoses also demonstrate excellent resistance to UV rays, abrasion and crushing.

The inner and outer layers are made of PVC, whose flexibility provides greater ease of use and handling. Flat storage helps reduce cluttering. After use, cleaning is easy, with no need for drying. The perfectly smooth inner surface decreases flow losses. The bright colours make identification easy.



Applications

- Water supply and irrigation

Sectors of Activity

- Farms
- Building trades and road works
- Industry

Connectors

Cam, semi-symmetrical or Storz connectors.

Band collars. In order to avoid damaging the hose during installation of the collars, it is recommended that before tightening. Each end be protected with a sleeve that can simply be a 10 cm length taken from the hose itself.

-10°C to +60°C

Standard quality. Blue cover.



- 1 Flexible PVC
- 2 Polyester fibre reinforcement
- 3 Black flexible PVC innertube

mm	± mm	mm	± mm	g/m	Bar	Bar	daN	Blue 25 m
25	+/- 1,5	2,2	+/- 0,2	240	30	10	350	TRI-140602
30	+/- 1,5	2,2	+/- 0,2	280	30	10	400	TRI-140631
35	+/- 1,5	2,2	+/- 0,2	300	30	10	500	TRI-140005
40	+/- 1,5	2,2	+/- 0,2	350	30	10	400	TRI-140027
45	+/- 1,5	2,2	+/- 0,2	400	30	10	450	TRI-140054
50	+/- 1,5	2,2	+/- 0,2	480	24	8	500	TRI-140070
55	+/- 1,5	2,2	+/- 0,2	500	21	7	550	TRI-140109
63	+/- 1,5	2,2	+/- 0,2	640	21	7	630	TRI-140125
75	+/- 2	2,4	+/- 0,2	750	21	7	750	TRI-140183
90	+/- 2	2,4	+/- 0,2	900	21	7	900	TRI-140212
100	+/- 2	2,4	+/- 0,2	1050	18	6	1000	TRI-140241
200	+/- 2	3,0	+/- 0,2	2100	7,5	2,5	2000	TRI-140676

