

CP8828 Pack

Powerful & Efficient

Benefits

- Torque reaction part in aluminium
- Charge gauge
- Rubber battery dampers absorb impacts and shocks
- Aluminium back and clutch housing
- Single-hand forward/reverse operation
- Ergonomic handle fits your hand perfectly
- Resistance to shock



Features

- 1/2" anvil with ring retainer
- Maximum torque: 775 ft.lb/1,050 Nm in reverse
- 6.9 lb/3.1 kg
- 9.5 in/243 mm length
- 20-Volt CP20XP Lithium-Ion 4Ah battery

Technical Description

Part Number	8941088480	
Model	CP8848 Pack	
Square Drive	1/2"	13mm
Square Drive	13mm	1/2"
Battery Voltage	20 V	
Ah	4 Ah	
Battery Type	4Ah 20V Lithium-ion	
Working Torque Range	68-950 Nm	50-700 ft.lbs
Maximum Torque (reverse)	1050 Nm	775 ft.lbs
Blows per Minute	2500	
Free Speed	1900 rpm	
Net Weight	3.1 kg	6.9 lb
Weight without Battery	2.43 kg	5.35 lb
Length	243mm	9.5"
Height	251mm	9.88"
Width	81mm	3.18"
Noise Level	89 db(A)	
Sound Power	100 db(A)	
Vibration K (EN-60745-1)	12.2 (2.3) m/s ²	
Vibration α (ISO-28927-2)	12.2 m/s ²	
Vibration K (ISO-28927-2)	2.3 m/s ²	