# **Tool Guard High Visibility, Corrosion Inhibitor**

# making the difference

# **Technical Data**

A light green, non-silicone, protective coating for use on mould tools. Removes moisture and provides long term protection to mould tool surfaces after use.

### **FEATURES**

- Easy identification, total coverage assured
- Will not penetrate or creep into the mould tool
- Easily moulded off, ensures quick start up
- Resists the effects of high humidity and acid finger marking

### **APPLICATIONS**

 All injection mould tools, blow mould tools, extrusion dies and metal components requiring corrosion protection

### **DIRECTIONS**

- Apply a light, even coating from 9" 12" (25 30 cm)
- Ensure that the surfaces have cooled to below 35°C to ensure optimum film formation
- Re-apply as necessary
- Can be removed with Ambersil Mould Solv

### **TECHNICAL DATA**

Appearance : Viscous, Green Film

Film Forming Properties : A continuous, homogenous film remains

after a cure time of 10 minutes

Solubility : Soluble in solvents, insoluble in water

Flammability : Classified as extremely flammable under

current EC Regulations

Flashpoint : Not applicable in sealed aerosol

Packaging : 500 ml aerosol (12 per carton)

## **STORAGE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below  $50^{\circ}$ C, away from direct heat and naked flame.



**PART NUMBER:** 31972-AA





### **HEALTH AND SAFETY**

Health and Safety sheet available separately.

### **TECHNICAL SERVICE**

Ambersil provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

### MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.