



Quick Release Pneumatic Hose Couplings



SSC Claw Couplings

SSC Hose Tail - DIN 3238 Part 3

- Extremely robust, durable coupling of forged steel, hardened, zinc plated and yellow passivated (free of chrome VI), equivalent to type Atlas Copco
- With oil-resistant rubber ring GOER, on request with steam-resistant rubber ring GDOR (up to 200°C) against extra charge
- Maximum bore for maximum flow capacity to reach full tool performance
- Turned gasket seat, therefore 100% tight
- Turned stem profile for perfect fit of the hose
- High quality coupling for compressed air in construction and industry



Working Pressure:
142 psi

Part No.	Hose I.D	DN	Temp	Material	Seal	Thread	Norm	Medium	Claw Distance
SSG10	3/8"	6.5	-40°C-+95°C	Malleable Iron/Steel	NBR	ISO 228	DIN 3238	Compressed Air	42 mm
SSG13	1/2"	10	-40°C-+95°C	Malleable Iron/Steel	NBR	ISO 228	DIN 3238	Compressed Air	42mm
SSG19	3/4"	15	-40°C-+95°C	Malleable Iron/Steel	NBR	ISO 238	DIN 3238	Compressed Air	42mm
SSG25	1"	18	-40°C-+95°C	Malleable Iron/Steel	NBR	ISO 238	DIN 3238	Compressed Air	42mm