

Brass/Steel

Nominal Diameter

5,5 = 25 mm²



Rectus Series


23

Low Pressure



Technical Description

1/4" industrial coupling according to ISO 6150 B and US MIL-SPEC 4109. Especially suitable for use with gaseous media in industry. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. Steel sleeve counters oscillating forces. The high insertion depth is guaranteed by an optimised plug guide.

Dust Protections  (P. 319)
for Coupling Part.-No. SK23S

Working Temperature*
-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.



Working Pressure**

35 bar
** maximum static working pressure with safety factor 4 to 1.

Material

Coupling: Brass / Steel nickel plated
Plug: Steel nickel plated or Brass
Seals: NBR

Interchangeability

- Industr. Interchange 1/4"
- US-MIL-SPEC-C-4109
- ISO 6150 B
- Rectus 24, 1400, 1423
- Cejn 310
- Hansen 3000
- Faster
- Gromelle 600
- Parker 20 1/4" + 30 1/4"
- JWL 521 + JWL 531

Flow diagrams

