

W2 ASFA 'L' Worm Drive Clips


MIKALOR

Thanks to the exclusive design of the housing, the ASFA "L" W2 hose clip has excellent performance while being at the same time very compact.

The cold-formed stamped band thread, smoothed on the underside, combined with the beveled band edges protects the hose from any damage.

The ASFA "L" W2 hose clip complies fully with the DIN 3017 norm and also with the RoHs directive EU 2002/95/EC dated 1st July 2006. This clip is ideal for general industrial applications.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling. Patented Worldwide.



ASFA "L" W2 Worm-Drive Clip (9mm bandwidth)

Application Ø		Part nº W2	L max.	s + 0,1 0	h max.	a + 0,3 a - 0,2	b max.	Max. Values* Torque (Nm)	Max. Values* Pressure (Bars)	Box Quantity (MOQ)	Packing
mm	inches										
8-12	5/16-15/32	0301650-8	17,5	0,65	8,4	7	10,9	1,5	30	200	1600
8-16	5/16-5/8	0301651-6	22,1	0,65	10,5	9	14,0	3,0	45	200	800
12-22	15/32-7/8	0301652-4	22,1	0,65	10,5	9	14,0	3,0	45	200	800
16-27	5/8-1-1/16	0301653-2	23,6	0,75	10,5	9	14,0	3,5	42	200	800
20-32	25/32-1-1/4	0301654-0	23,6	0,75	10,5	9	14,0	3,5	36	200	800
25-40	1-1-9/16	0301655-9	25,6	0,75	10,5	9	14,0	4,0	32	100	800
30-45	1-3/16-1-3/4	0301656-7	25,6	0,75	10,5	9	14,0	4,0	28	100	800
32-50	1-1/4-1-31/32	0301657-5	25,6	0,75	10,5	9	14,0	4,0	24	100	800
40-60	1-9/16-2-3/8	0301658-3	25,6	0,75	10,5	9	14,0	4,0	19	100	400
50-70	1-31/32-2-3/4	0301659-1	26,6	0,75	10,5	9	14,0	4,0	17	100	100
60-80	2-3/8-3-1/8	0301660-4	26,6	0,75	10,5	9	14,0	4,0	15	100	100
70-90	2-3/4-3-1/2	0301661-2	26,6	0,75	10,5	9	14,0	4,0	13	50	400
80-100	3-1/8-3-15/16	0301662-0	26,6	0,75	10,5	9	14,0	4,0	11	50	400
90-110	3-1/2-4-5/16	0301663-9	26,6	0,75	10,5	9	14,0	4,0	10	25	200
100-120	3-15/16-4-23/32	0301664-7	26,6	0,75	10,5	9	14,0	4,0	9	25	200
110-130	4-5/16-5-1/8	0301665-5	26,6	0,75	10,5	9	14,0	4,0	8	25	25
120-140	4-23/32-5-1/2	0301666-3	26,6	0,75	10,5	9	14,0	4,0	7	25	25
130-150	5-1/8-5-29/32	0301667-1	26,6	0,75	10,5	9	14,0	4,0	6	25	25
140-160	5-1/2-6-5/16	0301668-0	26,6	0,75	10,5	9	14,0	4,0	5	25	25

W2 Screw: Qst 36-3 Mild steel (DIN 1.0213) Silver-white Cr3 Zinc-Plated Band and Housing:
X6Cr17 Stainless steel (DIN 1.4016) (AISI-430)

