Micro IR-200 Infrared Thermometer



The RIDGID® micro IR-200 Non-Contact Infrared Thermometer provides simple, quick and accurate surface temperature readings at the push of a button. Simply squeeze the trigger and point the ultra-sharp dual class II lasers at the surface being measured.

- Ultra Sharp Dual Class II Lasers easily identify the surface area being measured.
- 30 To 1 Distance To Spot Ratio allows you to take more accurate measurements from a farther distance.
- · Adjustable Emissivity to accurately measure the temperature of virtually any surface.
- Audible and Visual High and Low Alarms quickly alert you to temperatures outside of the ranges that you set.
- Bright Backlit Display which can be toggled on in poorly lit areas.
- Tripod Mount Capable for repeatable, precise temperature measurements.





SPECIFICATIONS

Temperature Range	58° to 2192°F (-50° to 1200°C)
Measurement Accuracy	58°F to 68°F (-50°C to 20°C) ±4.5°F (2.5°C
	68°F ~2192°F (20°C ~1200°C)
	±1.0% or ±1.8°F (1.0°C)
Distance To Spot Ratio	30 to 1
Response Time	<150ms
• Emissivity	Adjustable, 0.10 - 1.00
Temperature Display	Curent Temperature, MAX Temperature
Measurement Units	Fahrenheit, Celsius
Power Source	Battery (1 x "9V") Included





CATALOG NO.	DESCRIPTION	WEIGHT KG
36798	micro IR-200 Non-Contact Infrared Thermometer	0.2



ALSO AVAILABLE FROM RIDGID



SR-20 Line Locator



ST-510 Transmitter



micro CD-100 Combustible Gas Detector



micro LM-100 Laser Distance Meter



SeeSnake® microReeITM Inspection System



micro CA-100 Inspection Camera