



# Silencers


## Coned Brass & Sintered Bronze Silencers

Code	A	F	B	H	dB
7000-1/8	1/8"	4.5	11.5	21.5	81
7000-1/4	1/4"	6	15	28	83
7000-3/8	3/8"	7	19	36	87
7000-1/2	1/2"	8	23	43.5	90
7000-3/4	3/4"	9	30	56	92 @ 4 bar
7000-1	1"	11	37	68.5	92 @ 4 bar

### Technical Characteristics

Maximum pressure: 10 bar  
 Minimum temperature: -10°C  
 Maximum temperature: +80°C  
 Filtration threshold: 50 µm

dB = Noise level in (dB) at 6 bar




Code	A	F	H	CH
7030-M5	M5	5	19.7	9
7030-1/8	1/8"	5.5	22.8	13
7030-1/4	1/4"	7	32.7	17
7030-3/8	3/8"	9	41.7	22
7030-1/2	1/2"	10	48.5	24
7030-3/4	3/4"	11	57	30
7030-1	1"	14	70	36

### Technical Characteristics

Maximum pressure: 10 bar  
 Minimum temperature: -10°C  
 Maximum temperature: +80°C  
 Filtration threshold: 50 µm

dB = Noise level in (dB) at 6 bar




Code	A	F	H	CH	dB
7040-1/8	1/8"	8	42	14	76
7040-1/4	1/4"	8	52	17	75
7040-3/8	3/8"	10	54	22	88
7040-1/2	1/2"	12	65	27	89
7040-3/4	3/4"	9	65	30	

### Technical Characteristics

Maximum pressure: 12 bar  
 Minimum temperature: -10°C  
 Maximum temperature: +80°C  
 Filtration threshold: 36 µm

dB = Noise level in (dB) at 6 bar




## Flat Brass & Sintered Bronze Silencers

Code	A	F	H	CH	dB
7010-1/8	1/8"	6	14	13	73
7010-1/4	1/4"	7	17	16	74
7010-3/8	3/8"	8	18	19	85
7010-1/2	1/2"	10	20	24	89
7010-3/4	3/4"	10	23	30	90

### Technical Characteristics

**Maximum pressure:** 12 bar  
**Minimum temperature:** -10°C  
**Maximum temperature:** +80°C  
**Filtration threshold:** 100 µm

dB = Noise level in (dB) at 6 bar




Code	A	F	H	CH	dB
7020-M5	M5	4	9	8	
7020-1/8	1/8"	6	15	13	74
7020-1/4	1/4"	7	18	16	72
7020-3/8	3/8"	8	20	19	88
7020-1/2	1/2"	10	22	24	90
7020-3/4	3/4"	10	26	30	90

### Technical Characteristics

**Maximum pressure:** 12 bar  
**Minimum temperature:** -10°C  
**Maximum temperature:** +80°C  
**Filtration threshold:** 100 µm

dB = Noise level in (dB) at 6 bar



Code	A	H
7120-1/8	1/8"	4
7120-1/4	1/4"	6
7120-3/8	3/8"	6
7120-1/2	1/2"	9
7120-3/4	3/4"	10
7120-1	1"	10

### Technical Characteristics

**Maximum pressure:** 12 bar  
**Minimum temperature:** -10°C  
**Maximum temperature:** +80°C  
**Filtration threshold:** 120 µm

dB = Noise level in (dB) at 6 bar

