

Industrial Stable Steps



Product Dimensions

| Product Code | Tread Count | Approximate Working Height* (m) | Platform Height (mm) | Platform Width (mm) | Platform Depth (mm) | Depth (mm) | Width (mm) | Closed Height (mm) | Weight (kg) |
|---------------|-------------|---------------------------------|----------------------|---------------------|---------------------|------------|------------|--------------------|-------------|
| LADD-1271-101 | 1 | 1.8 | 220 | 490 | 250 | 393 | 600 | 220 | 2.1 |
| LADD-1271-102 | 2 | 2.1 | 504 | 484 | 200 | 530 | 740 | 504 | 5.2 |
| LADD-1271-103 | 3 | 2.4 | 750 | 550 | 200 | 770 | 780 | 750 | 8.5 |
| LADD-1271-104 | 4 | 2.6 | 1000 | 550 | 200 | 970 | 780 | 1000 | 12.0 |

Technical Description

Stable Steps provide safe and comfortable access to a range of apparatus in industrial environments. The high strength, welded tubular construction ensures stability and long service life with maximum stability thanks to the wide standing surface. The robust construction means they are a solid stationary solution that remains both lightweight and portable as required.

- High strength welded aluminium construction
- 500 x 250mm staircase like treads
- Comfortable wide standing surface

Standards & Classification

- Maximum static vertical load (MSVL): 150kg
- EN14183

Warranty

- 5 years

Shipping Dimensions

| Product Code | Shipping Length (mm) | Shipping Width (mm) | Shipping Depth (mm) | Shipping Volume (m ³) | Shipping Weight (gross kg) | Barcode |
|---------------|----------------------|---------------------|---------------------|-----------------------------------|----------------------------|---------------|
| LADD-1271-101 | 220 | 600 | 393 | 0.0519 | 2.1 | 5060356910861 |
| LADD-1271-102 | 504 | 740 | 530 | 0.1977 | 5.2 | 5060356910878 |
| LADD-1271-103 | 750 | 780 | 770 | 0.4505 | 8.5 | 5060356910885 |
| LADD-1271-104 | 1000 | 780 | 970 | 0.7566 | 12.0 | 5060356910892 |

Technical Description

Stable Steps provide safe and comfortable access to a range of apparatus in industrial environments. The high-strength, welded tubular construction ensures stability and long service life with maximum stability thanks to the wide standing surface. The robust construction means they are a solid stationary solution that remains both lightweight and portable as required.

- High strength welded aluminium construction
- 500 x 250mm staircase like treads
- Comfortable wide standing surface

Standards & Classification

- Maximum Static Vertical Load (MSVL) 150kg
- EN14183

Warranty

- 5 Years

Shipping Dimensions

| PRODUCT SKU | SHIPPING LENGTH (MM) | SHIPPING WIDTH (MM) | SHIPPING DEPTH (MM) | SHIPPING VOLUME (M ³) | SHIPPING WEIGHT (GROSS KG) | BARCODE |
|-------------|----------------------|---------------------|---------------------|-----------------------------------|----------------------------|---------------|
| 1271-101 | 220 | 600 | 393 | 0.0519 | 2.1 | 5060356910881 |
| 1271-102 | 504 | 740 | 530 | 0.1977 | 5.2 | 5060356910878 |
| 1271-103 | 750 | 780 | 770 | 0.4505 | 8.5 | 5060356910885 |
| 1271-104 | 1000 | 780 | 970 | 0.7566 | 12.0 | 5060356910892 |