# **Spatter Release**

# making the difference

## **Technical Data**



**SPATTER RELEASE** is the traditional anti-spatter formulation, which has been developed specifically to exclude the use of any silicones or flammable solvents.

#### **APPLICATIONS**

Spatter Release is non-flammable and economical in use. Ideal for numerous industries:

- Automotive Manufacture and Repair
- Heavy Plant Manufacture
- Shipbuilding and Dockyards
- Construction

- Office Furniture
- Agriculture
- Tool Manufacturers
- Fork Lift Trucks

Prevents spatter adhesion on welding equipment, workpieces, surfaces, jigs and surrounding areas. Apply a light, even film from 9" - 12" (25 - 30 cm). Do not overapply.

After welding, the film can be wiped away very easily and leaves no residues. Post-welding applications (e.g. painting) can then be carried out without interference.

#### **TECHNICAL DATA**

Appearance : Clear, colourless liquid

Odour : Strongly ethereal

SG @ 25°C : 1.3

Pressure @ 25°C : 7 - 8 Bar

Discharge rate : 2.3 g/sec

Solubility : Soluble in solvents, insoluble in water

Flammability : Non-flammable

Flashpoint : Not applicable in sealed aerosol

Packaging : 450g/346ml (12 per carton)



**PART NUMBER:** 6190004150



#### **STORAGE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below  $50^{\circ}$ C, away from direct heat and naked flame.

### **HEALTH AND SAFETY**

Health and Safety sheet available separately.

#### **TECHNICAL SERVICE**

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

# MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.