


CP SIL 460



Clamp profile hose (clip hose), (up to +280°C)

Applications

- flexible hose/ ducting for hot and cold gases and for dust, powder, fibres
- high temperature extraction: oven, foundry, furnace, smelting, ceramics industry, glass industry, steel plant, aluminium mill

Properties

- abrasion protection via external clamp profile
- secure clamping of the wall within the clamp profile
- highly flexible + compressible 4:1
- very good heat resistance
- flame-retardant according to: DIN 4102-B1
- conforms to RoHS guideline

Temperature Range

- 70°C to 260°C
- short time to 280°C

Design, Material

CP construction

- clamp profile supporting spiral: galvanised steel
- wall: Silicon coated glass fabric

Delivery variants

- further diameters and lengths available on request
- stainless steel (INOX) clamp profile
- double-layer

I.D. in / mm	O.D. mm	Over- pressure bar	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Order No.
2 / 50-51	62	0,525	0,300	18	0,680	6	460-0050-0000
- / 55	67	0,500	0,280	20	0,740	6	460-0055-0000
2,36 / 60	72	0,480	0,250	20	0,800	6	460-0060-0000
2,5 / 63-65	77	0,460	0,230	22	0,860	6	460-0065-0000
- / 70	82	0,440	0,210	22	0,920	6	460-0070-0000
3 / 75-76	87	0,420	0,180	24	0,980	6	460-0075-0000
- / 80	92	0,405	0,160	24	1,040	6	460-0080-0000
3,5 / 89-90	102	0,375	0,110	26	1,160	6	460-0090-0000
4 / 100-102	112	0,250	0,100	28	0,950	6	460-0100-0000
- / 110	122	0,240	0,085	30	1,040	3 6	460-0110-0000
4,5 / 114-115	127	0,230	0,080	32	1,090	3 6	460-0115-0000
4,72 / 120	132	0,225	0,075	32	1,130	3 6	460-0120-0000
5 / 125-127	137	0,220	0,070	34	1,180	3 6	460-0125-0000
- / 130	142	0,215	0,060	34	1,220	3 6	460-0130-0000
5,5 / 140	152	0,205	0,050	36	1,310	3 6	460-0140-0000
6 / 150-152	162	0,140	0,040	38	0,950	3 6	460-0150-0000
6,3 / 160	172	0,135	0,035	40	1,010	3 6	460-0160-0000
6,5 / 165	177	0,130	0,035	41	1,040	3 6	460-0165-0000
- / 170	182	0,130	0,035	42	1,070	3 6	460-0170-0000
- / 175	187	0,125	0,030	44	1,100	3 6	460-0175-0000
7 / 178-180	192	0,125	0,030	44	1,130	3 6	460-0180-0000
8 / 200-203	212	0,115	0,025	48	1,250	3 6	460-0200-0000
- / 215	227	0,110	0,020	52	1,340	3 6	460-0215-0000
- / 225	237	0,110	0,020	54	1,400	3 6	460-0225-0000
9 / 228-229	240	0,110	0,020	54	1,460	3 6	460-0228-0000
- / 250	262	0,080	0,020	58	1,560	3 6	460-0250-0000
10 / 254	266	0,080	0,020	60	1,590	3 6	460-0254-0000
- / 275	287	0,075	0,015	64	1,710	3 6	460-0275-0000
11 / 280	292	0,075	0,015	65	1,740	3 6	460-0280-0000
- / 300	312	0,070	0,010	68	1,860	3 6	460-0300-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.

I.D. in / mm	O.D. mm	Over- pressure bar	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Order No.
12 / 305	317	0,070	0,010	69	1,890	3 6	460-0305-0000
- / 315	327	0,070	0,010	71	1,950	3 6	460-0315-0000
- / 325	337	0,070	0,010	74	2,030	3 6	460-0325-0000
13 / 330	342	0,065	0,010	75	2,070	3 6	460-0330-0000
- / 350	362	0,055	0,010	78	2,160	3 6	460-0350-0000
14 / 356	368	0,055	0,010	80	2,190	3 6	460-0356-0000
- / 375	387	0,050	0,010	83	2,260	3 6	460-0375-0000
- / 400	412	0,050	0,010	88	2,470	3 6	460-0400-0000
16 / 405-406	418	0,050	0,010	90	2,510	3 6	460-0406-0000
- / 450	462	0,045	0,005	98	2,770	3 6	460-0450-0000
18 / 457	469	0,045	0,005	100	2,810	3 6	460-0457-0000
- / 500	512	0,040	0,005	108	3,070	3 6	460-0500-0000
20 / 508	520	0,030	0,005	110	3,120	3 6	460-0508-0000
- / 600	612	0,025	0,005	128	3,680	3	460-0600-0000
24 / 610	622	0,025	0,005	130	3,740	3	460-0610-0000
- / 700	712	0,020	0,002	148	4,290	3	460-0700-0000
28 / 712	724	0,020	0,002	151	4,360	3	460-0712-0000
- / 750	762	0,020	0,001	158	4,600	3	460-0750-0000
- / 800	812	0,020	0,001	168	4,900	3	460-0800-0000
32 / 813-815	827	0,020	0,001	171	4,990	3	460-0815-0000
- / 900	912	0,020	0,001	188	5,500	3	460-0900-0000
36 / 915	927	0,020	0,001	191	5,590	3	460-0915-0000
- / 1000	1012	0,015	0,001	208	6,110	3	460-1000-0000
40 / 1016	1028	0,015	0,001	213	6,200	3	460-1016-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional technical data at www.norres.com/en/technology/

Accessories




CLAMP 212



CLAMP 217



CLAMP 213



CONNECT 228



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.