Silicone Anti-stick

ambersi making the difference

Technical Data



SILICONE ANTI-STICK is an anti-stick and slip inducing surface lubricant. It is based on a high purity, highly concentrated silicone oil for maximum materials compatibility, exceptional slip, and long-lasting performance. The higher concentration of silicone oil allows sliding surfaces to operate at elevated speeds or at higher loads.

- Ideal for plastic-plastic surface lubrication
- Long-lasting for reduced re-lubrication requirements
- Excellent materials compatibility
- Use on rapidly oscillating sliding surfaces
- Excellent operation temperature range

WRAS APPRODUCT

Apply a light, even coating from 9" - 12" (25 - 30 cm). Re-apply as necessary.

TECHNICAL DATA

Appearance : Clear, colourless liquid

Odour : Hydrocarbon

SG @ 25°C : 0.775

Pressure @ 25°C : 2.6 Bar

Discharge rate : 1.4 g/sec

Temperature range : Operational up to 200°C

Solubility : Soluble in solvents, insoluble in water

Flammability : Classified as extremely flammable under

current EC Regulations

Flashpoint : Not applicable in sealed aerosol

Packaging : 400 ml aerosol (12 per carton)



PART NUMBER: 6140001500



STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50° C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.