


CONNECT 227



Soft sleeve for EVA hoses

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable
- good resistance to alkalis and acids
- good resistance to chemicals
- conforms to RoHS guideline

Temperature Range

- -20°C to 70°C
- short time to 80°C

Design, Material

Wall: premium polyethylene (PE), Wall of EC version electrically conductive <math><10^5 \Omega</math>; electrically conductive premium PE

Delivery variants

- further diameters available on request
- grey (standard)
- black (standard)

Suitable for hose

EVA: 373; 373 (AS / EC)

Rec. Adapter Ø mm	Rec. Adapter length mm	Threading depth Hose mm	Total Length mm	Weight kg/Pcs	Suitable for Hose I.D. mm	Order No.
Colour grey						
32	44	40	85	0,060	32	227-0032-0000
38	44	40	85	0,070	38	227-0038-0000
50	49	41	90	0,090	50	227-0050-0000
Colour black						
32	44	40	85	0,060	32	227-0032-0001
38	44	40	85	0,070	38	227-0038-0001
45	44	40	90	0,080	45	227-0045-0001
50	49	41	90	0,090	50	227-0050-0001
Electrically conductive <math><10^4 \Omega</math> Colour black						
32	44	40	85	0,060	32	227-0032-1003
38	44	40	85	0,070	38	227-0038-1003
50	49	41	90	0,090	50	227-0050-1003

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 20°C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.