

MSV Series Castors

- Medium duty range
- Pressed steel bracket
- Wheel sizes from 80mm to 200mm
- Load capacities starting from 130kg up to 350kg



White Nylon Tyre

Wheel Diameter (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Capacity (kg)	Swivel	Swivel Braked	Fixed
100	36	RB	105 x 80	80 x 60	40	128	150	MSV100NY1B	MSV100NY1BSWB	MFV100NY1B
125	40	RB	105 x 80	80 x 60	40	155	200	MSV125NY1B	MSV125NY1BSWB	MFV125NY1B
160	50	RB	135 x 110	105 x 80	55	195	300	MSV160NY1B	MSV160NY1BSWB	MFV160NY1B



Red Polyurethane Tyre, Nylon Centre

Wheel Diameter (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Capacity (kg)	Swivel	Swivel Braked	Fixed
100	32	RB	105 x 80	80 x 60	40	128	150	MSV100PN1B	MSV100PN1BSWB	MFV100PN1B
125	32	RB	105 x 80	80 x 60	40	155	200	MSV125PN1B	MSV125PN1BSWB	MFV125PN1B
160	40	RB	135 x 110	105 x 80	55	195	300	MSV160PN1B	MSV160PN1BSWB	MFV160PN1B



Blue Rubber Tyre, Nylon Centre

Wheel Diameter (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Capacity (kg)	Swivel	Swivel Braked	Fixed
100	36	RB	105 x 80	80 x 60	40	128	160	MSV100RN1B	MSV100RN1BSWB	MFV100RN1B
125	38	RB	105 x 80	80 x 60	40	155	200	MSV125RN1B	MSV125RN1BSWB	MFV125RN1B
160	46	RB	135 x 110	105 x 80	55	195	300	MSV160RN1B	MSV160RN1BSWB	MFV160RN1B