

Safety Couplings

XF Safety Couplings



Designed to conform with compressed air Health & Safety Guide HS(G)39. See also ISO 4414:1998 and EN 983:1996 for safety requirements covering the installation and use of pneumatic equipment.

Key Product Benefits

- Two stage self-venting release
- Creates a safe compressed air environment
- Compatible with XF adaptors
- Safe and simple to use
- Best practice for compressed air users
- Enhances workshop safety - prevents hose whip

Specifications

Nominal bore	7.4 mm	
Flow rate @ 6 bar	1750 l/min @ 0.5 bar p.d.	
Maximum Working Pressure	230 lbf/in ²	16 bar
Interchangeability	Rectus 25/26	
	Legris 25/26	
	Cejn 320	
	Norgren 234/238	
	Schrader InterCheck 35	

Approvals

Conforms to ISO 4414:1998 and EN 983:1996

Product Safety Information

Safety Couplings

Product Options

Part No.	Description	Thread Type	Thread Size
AS71CM	XF Safety Coupling	Male	G 1/4
AS71EM	XF Safety Coupling	Male	G 3/8
AS71CF	XF Safety Coupling	Female	G 1/4
AS71JM	XF Safety Coupling	Male	G 1/2
AS71EF	XF Safety Coupling	Female	G 3/8
AS71JF	XF Safety Coupling	Female	G 1/2