

Compact and affordable, the Swifty Bagger Junior is designed to automatically open, fill and seal premade laminated pouches in varying styles including pillow, doy and quad bags.

Features

- Omron PLC
- Omron PID temperature controller
- Color touchscreen
- SMC vacuum generator
- Quick bag loading station with vacuum mechanism
- No bag—no fill sensor
- · 304 stainless steel frame

Electrical

- North American 230 VAC / 1 Ph / 60 Hz
- International 240 VAC / 1 Ph / 50 Hz
 All other electrical specifications available
- on request at additional cost

Air

- North American 20 CFM / 90 PSI
- International 600 L / min / 6 bar

Bag Width

• 5.5 to 11 inches (130 to 280 mm)

Bag Length

• 5.5 to 15 inches (130 to 380 mm)











Stand-up doy

*Final bag style specific to order and sales offer specifications





DESIGN

The Swifty Bagger Junior's compact footprint and open design make it easy to set up, operate, clean and and service.



BAG FEEDING

Easy to adjust bag magazine ensures that premade bags enter the machine perfectly square, resulting in consistent output and seals



CLEANING / SANITATION

Simply open the clear Lexan front doors and access all bag filling components to clean in a matter of minutes with only one person.



EASILY INTEGRATE

The Swifty Bagger integrates with any auxiliary filling machines including our PrimoCombi multi-head weigher, PrimoLinear net weigher and Star Auger for powders.



*Bags must open in round / oval shape, no box opening bags *Bags with zipper closure must be pre-opened by supplier *Bags must be rigid enough to be able to stack in magazine *Specifications subject to change without notice

00



Quality construction & state-of-the-art technology at reasonable prices