

19" ELECTROBLOCK with 6 French sockets, with RCD

REF. F2036/14



BASIC INFORMATION

DESCRIPTION

Manufactured with high-quality aluminum, the profile has been specially designed to withstand the high temperatures inside rack cabinets. The Electroblock's mounting flaps allow for multiple fixing positions within the rack, optimizing its internal space. The Electroblock is supplied pre-wired internally, with an instruction manual, and includes mounting brackets for the rack cabinet. It is designed to power any electrical or electronic device housed inside the rack cabinet: hubs, switches, repeaters, routers, etc. It measures 1U in height (44.45 mm) to maximize space inside the cabinet and ensure compliance with IEC 60297 standards. The Electroblock is supplied pre-wired internally, with an instruction manual, and includes mounting brackets for the rack cabinet.

MATERIAL

Aluminium

COMPATIBILITY

19" Racks

ETIM CLASS

EC000330

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)

Up to 25 mm

FORMAT

DIN

BREAKING CAPACITY (A)

10000 A (with upstream fuse)

CURRENT (A)

25 A / 30 mA

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436025707

PRODUCT NET WEIGHT

0.86

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

2750000

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436025707

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.86

UNITARY PACKAGING VOLUME

2750000

PACKAGING HEIGHT

55

PACKAGING NET WEIGHT

0.86

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING WIDTH

500

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.86

PACKAGING LENGTH

100