

Flat voice and data plate with dust cover for 2 RJ45 Nexans® for 1 element graphite Simon 500 Cima

REF. 50018089-038



BASIC INFORMATION

DESCRIPTION

A good connection is fundamental in current times, but a successful installation it will save us time and money with any mishap that may arise. The system of connections 500 Cima, Simon offers us a new click terminal connection, simple and safe, for greater security in the installations. This series also has a vast range of mechanisms for any type of connection, whether electrical, voice, data or multimedia. Simon makes available to our solutions for any type of ambience, always with an appearance stylish and modern. As this plate for voice and data connections, one element and two Nexans ® RJ45 connectors. It has a graphite finish, with dust cover, it has a flat plate and includes a snap-fit to fix in wrappers. It is also manufacturing with the best materials and thermoplastic components halogen-free, fireproof, self-extinguishing.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Nexans® LANmark®-5 EVO, LANmark®-6 EVO.

IP RATING

IP20

RAL

7021

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Not included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

RJ45 Nexans® connectors

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

SNAP-FIT TYPE

RJ45 Nexans® connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

26

UNITARY PACKAGING GROSS WEIGHT

0.028

PACKAGING LENGTH

86

UNITARY PACKAGING WIDTH

58

PRODUCT NET WEIGHT

0.028

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING LENGTH

86

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.604

UNITARY PACKAGING MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053097083

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

129688

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

26

PACKAGING NET WEIGHT

0.28

PACKAGING WIDTH

58

PACKAGING WEIGHT UNIT

KGM

