Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e UTP black Simon K45

REF. **KA95U/14**



BASIC INFORMATION

DESCRIPTION

Voice and data flat plate of the series Simon K45. It incorporates a dust cover and has an element and an RJ45 connector of category 5e UTP, finished in black colour, this is the individual version of the plate with four modules. To perform the connection of the same, it is necessary to use the insertion tool. This voice and data plate is available for both one as for two RJ45 connectors. It incorporates a dust shutter and allows the combination of the same in vertical enclosures. To do this, it is necessary to take the 90 ° positioner (ref. K66). The series Simon K45 commitment compact products, ideal for use in environments very varied. This plate measures 45x45 mm and has a depth of 30 mm requires a wire cross-section 22-26 AWG. It is possible to its installation in surface-mounted or recessed. The series Simon K45 has been made with components of the highest quality, that guarantee the security of its products. This plate of voice and data is designed to calve of metal materials isolated thermoplastically. In the event of smoke generation, the toxicity would be minimum. In addition to withstand high temperatures, plates of the series Simon K45, are easy to maintain, just a soft cloth to clean always keep them.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Voice and data flat plate with dust cover and RJ45 category 5e UTP connector

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-26 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 5e UTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+60º C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-5 to 60º C

NUMBER OF MODULES
Four

PLATE TYPE
Flat

RAL
7021

RJ45 ADAPTOR MODULE
Supplied with the voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0.3

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.022

PRODUCT NET WEIGHT

0.022

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436046085

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

70

PACKAGING WIDTH

93

PACKAGING LENGTH

140

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

911400

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.22

PACKAGING NET WEIGHT

0.22

PACKAGING WEIGHT UNIT

KGM