

Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 6 FTP aluminium Simon K45

REF. KA96F/8



BASIC INFORMATION

DESCRIPTION

Model of plate for KA96F / 8 Voice and data connections, forming part of the range of Simon components K compatible With the use of other elements and components of the same range. It is a plate of voice and Data version plate with dust cover with 1 element for 1 RJ45 connector of Category 6 FTP with snap-fit Keystone I, II, ATT ® / Avaya ® with insertion tool. Number of modules quarter full with colour and finishes In graphite. It is compatible with element 90° positioner (ref. K66) to guide the plate into a vertical position. Composed Metal components with self-extinguishing thermoplastic insulation And halogen-free; guarantees no flame propagation in case of Fire and the low toxicity, ensuring maximum security professionally. It measures 45x45mm and 42,9mm, ideal to adapt to any kind of systems and installations in Different environments.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

RJ45 CONNECTION

With insertion tool

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

Category 6 FTP

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

MAX TEMP DURING

CONSTRUCTION WORK (°C)

+60° C

NUMBER OF MODULES

Four

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.032

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046214

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.32

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.16

UNITARY PACKAGING GROSS
WEIGHT

0.032

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140