

Downlight 800.21 Black 15W 3000K DALI2

REF. 80021338-683



BASIC INFORMATION

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Units

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

1100 lm/15W

IP RATING

IP54

ELECTRICAL CLASS

tipo 2

OPTICS

Extensive

OPERATING TEMPERATURE RANGE (°C)

-15°C a 35°C

L70 (°C)

50.000 h a 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Categoría exento

POWER SUPPLY (V~)

220/240 V~

LIGHT BEAM APERTURE ANGLE (°)

60°

POWER (W)

15W

COLOR TEMPERATURE (K)

3000K

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CONTROL

DALI2

LIGHTING EFFICIENCY (LM/W)

80 lm/W

COS Φ

0.95

LUMENS (LM)

1100 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

80

INSTALLATION TYPE

Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50.000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053307953

PACKAGING VOLUME
3272500

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
1

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
110

PACKAGING GROSS WEIGHT
0.426

UNITARY PACKAGING GROSS
WEIGHT
0.312

PACKAGING WIDTH
170

PACKAGING NET WEIGHT
0.312

PRODUCT NET WEIGHT
0.312

PACKAGING LENGTH
175

PACKAGING WEIGHT UNIT
KGM