

Complete kit with 4 schuko socket outlets and plate for 4 RJ45 connectors white S400 Top

REF. 42604040-130



BASIC INFORMATION

DESCRIPTION

Desk top complete kit with 4 Schuko socket outlets and plate for 4 RJ45 connectors, white in colour and belonging to the series Simon 400 Top. Its dimensions are 295 x 120 x 80 mm and its type manual elevation and has a current of 16 A and works with a voltage of 250V. To install the kit, can be done by flush mounted in furniture, using the claws that incorporates and to complete the installation of the product, it must be combined with the Simon 400 Top (references 400XXX-03X) and the installation is always you must perform in places with a temperature of between -5 to 60 ° C, approximately. The enclosure of the kit is made of painted steel, the profile in anodised aluminium and the enclosure of painted steel and the covers and fastenings in self-extinguishing thermoplastic and halogen-free. Its cleaning is very easy to perform since it will only need to wipe it with a soft and dry cloth, without resorting never with abrasive cleaners or cloths containing chlorine.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

RAL

9016

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP30

NUMBER OF RJ45 WINDOWS

4

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

FORMAT

Schuko

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

SNAP-FIT TYPE

Keystone I, II and Systimax

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

NUMBER OF SOCKETS

4 sockets for standard current circuit

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

VERSION

6 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196137

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.075

PRODUCT NET WEIGHT

1.075

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053196137

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

95

PACKAGING WIDTH

125

PACKAGING LENGTH

330

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.075

PACKAGING WEIGHT UNIT

KGM