

**Customisable kit with cover and brush, 2xUSB charger, 2  
schuko socket outlets and 1 empty element black S400  
Indesk**

REF. 44422000-138



## BASIC INFORMATION

### DESCRIPTION

Kit within the table customizable, of the series Simon 400 Indesk, black in colour and with cover, brush strip, 2 USB chargers, 2 bases for Schuko socket outlets and 1 element empty. It is installed by flush mounted in furniture and to fix it only have to use the claws that includes the kit or also screws, which have to position, place in the holes available. Its dimensions are 295 x 185 x 85 mm and its manufacturing materials are used the following: Painted steel for the enclosure, anodised aluminium profile and in self-extinguishing thermoplastic and halogen-free that favours no flame spread in case of fire, in case of fire and low toxicity in case of smoke. To clean this kit will only need to wipe it with a soft and dry cloth and never use abrasive cloths or cleaners with chlorine.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

### NUMBER OF POSSIBLE ELEMENTS

1

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### IK CLASSIFICATION

07

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

### OPERATING TEMPERATURE RANGE (°C)

-5...+60

### TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9005

### NUMBER OF REAR ENTRANCES

1

### RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

### NUMBER OF SOCKETS

2 sockets for standard current circuit

### NUMBER OF USB CHARGERS

1

### VERSION

4 elements

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With brush

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS

1

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45°

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2014/30/UE EMC;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;EN 60950-1:2006;EN 60950-1:2006 A11:2009;EN 60950-1:2006 A1:2010;EN 60950-1:2006 A12:2011;EN 60950-1:2006 A2:2011\*3;ETSI-EN 301489-34 V1.4.1;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053196359

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.78

### PRODUCT NET WEIGHT

1.78

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053196359

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

275

### PACKAGING WIDTH

192

### PACKAGING LENGTH

95

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

5016000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.78

### PACKAGING WEIGHT UNIT

KGM