

Waterproof luminaire 840 IP65 NW 1200 mm

REF. 84030038-884



BASIC INFORMATION

DESCRIPTION

For general lighting and long duration, the collection Simon puts at your disposal, the luminaire waterproof 840 IP65 for with system to protect her of the entry of external agents such as water or dust. With control of switching on ON-OFF and connectors Power IN / OUT, it is designed to light large commercial warehouses, such as car parks and industrial zones. It has a colour temperature of 4000 K, for a white tone of a neutral NW, and a performance of 4100 lm with 40 W consumption of luminaire. It is also compatible with a power of 230 Volt voltage and 50 Hz, with a service life of 30,000 at 25 ° C and a maximum of 35 °C. With finishes in black and a dimension 1200 x 75 x 78mm, it has an installation flexible and designed for surface-mounted, both in the ceiling and wall, with a capacity of interconnection of up to 16 Amps.

DIFFUSER MATERIAL

Polycarbonate

APPLICATION

Car park lighting,Industrial lighting

PACKAGING CONTENTS

1 unit

LENS MATERIAL

Polycarbonate

ETIM CLASS

EC002892

REMARKS

Flexible installation, interconnection up to 16 amps.

TECHNICAL INFORMATION

FREQUENCY

50 Hz

COS Φ

0.97

LIGHTING EFFICIENCY (LM/W)

102 lm/W

IK CLASSIFICATION

08

CRI

80

LUMENS (LM)

4100 lm

IP RATING

IP65

DIRECTIONAL

No

LUMENS/W

4100 lm/40W

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum temperature

DRIVER INCLUDED

Yes

OPTICS

General

POWER SUPPLY (V~)

230 V~

ELECTRICAL CLASS

Type 1

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

4000 K

L70 (°C)

30,000 h at 25 °C

POWER (W)

40 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Suspended

INSTALLATION TYPE

Surface

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.52

PRODUCT NET WEIGHT

1.22

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053146491

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

1265

PACKAGING WIDTH

85

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9677250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.22

PACKAGING WEIGHT UNIT

KGM