

Hinged cover for adjustable floor box or service cover in concrete or raised floor for 2 elements grey Simon 500 Cima

REF. RSF001/1



BASIC INFORMATION

DESCRIPTION

Manufactured with metal components with self-extinguishing and halogen-free thermoplastic insulation., a material that guarantees no flame propagation in case of fire and the low toxicity in case of smoke, the Hinged cover for adjustable floor box or service cover in concrete or raised floor with two elements in grey colour of the Simon 500 Cima series combines the most innovative design with the classic lines that define the accessories designed for the electrical systems of homes and companies. With dimensions of 105 x 161 x 15 mm, its installation can be levarse out easily in concrete floor and raised floor through the adjustable floor boxes or inspection covers. Also, the adjustable floor boxes include the hinged lid, so that it is only necessary to request it as a replacement part in the event of breakage or loss.

FINISH

Grey

PACKAGING CONTENTS

Hinged cover

MATERIAL

Plastic

ETIM CLASS

EC001903

REMARKS

The adjustable floor boxes include the hinged cover. Only necessary to order it as a replacement part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

2 modules

RAL

7011

VERSION

2 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Via coupling pin supplied on the cover

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

In raised or concrete floor with adjustable floor boxes or service covers

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056183

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.346

PRODUCT NET WEIGHT

0.346

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436056183

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

20

PACKAGING WIDTH

220

PACKAGING LENGTH

150

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.66

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.346

PACKAGING WEIGHT UNIT

KGM