# BNC connector 75 Ohms female with trim plate white Simon K45

REF. **K102D/9**



## BASIC INFORMATION

### DESCRIPTION

The BNC 75 Ohms female is part of the series of Simon K45 and is included a trim plate. It has a in a classic colour white that facilitates its integration anywhere in the room of the home, office or premises where it is. Its installation is very simple and can be carried out either by flush mounted or instalándolo directly in surface-mounted. Its dimensions are 22.5 x 45 millimetres. Its type of clamping is by welding and its type of operation is by insertion. Simon advises, bear in mind that the maximum length of cabling recomendaba for this connector if it is wire RG-6, is 90 metres. The connector is manufactured with metal components with self-extinguishing and halogen-free thermoplastic insulation.. This means that contributes to of fire propagation in case of fire and that reduces the toxicity of smoke, which gives much security to the final set.

### FINISH

White

### COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

### PACKAGING CONTENTS

BNC 75 Ohms female connector

### ETIM CLASS

EC000018

### REMARKS

Maximum wire length recommended; 90 metres (RG-6 cable). For additional information, please read the product instruction sheet

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

### CONNECTOR TYPE
BNC

### NUMBER OF CONTACTS
1

### NUMBER OF POSSIBLE ELEMENTS
1/2 element

### FORMAT
BNC

### IP RATING
IP20

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

### RAL
9003

### STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

### VERSION
Single

### NUMBER OF WIRES
2

## INSTALLATION AND MAINTENANCE

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

### INSTALLATION TYPE
Suitable for surface and flush mounting

## REGULATIONS

### REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.015

PRODUCT NET WEIGHT
0.015

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436046924

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.15

PACKAGING NET WEIGHT
0.15

PACKAGING WEIGHT UNIT
KGM